

DP1900 Ink Delivery System

Digital Print Ltd's range of High-Flow, Low-Flow and End Shooter Ink delivery systems. Suitable for a wide range of Inkjet printheads and is suitable to use with Aqueous, UV and oil based inks. Header tanks are provided depending on system requirements.

- Works with most types of printheads
- Touch screen HMI
- Windows GUI and SCADA options
- Aqueous, UV and Oil based inks
- Single and Dual Header tanks available
- Optional external Stainless Steel Ink tank





Contact Us


Email: sales@digitalprintltd.com Phone: +44 (0)1604 866254

Website: www.digitalprintltd.com

DP1900 Specifications



Above: Touchscreen HMI



Above: Windows GUI screen

- Suitable for DOD Piezo crystal inkjet heads
- Suitable for use with Aqueous, UV and Oil inks
- Supply Ink tank level display
- Easily adjust settings
- Graphical display of meniscus
- Max purge pressure of 1.9 Bar

Dimensions				
	Ink System	Touchscreen HMI		
Height	382mm	121mm		
Width	254mm	175mm		
Depth	121mm	60mm		

Electrical Specifications				
Voltage	Amps	Frequency		
110/240 AC	2	50/60		

Ink Tank Specifications					
Capacity	Height	Width/Depth			
1.6L	290mm	180mm			

Ink System Options				
	De-Gas	Scada	НМІ	PC
DP-ES1900 -	✓	✓	✓	✓
DP-LF1900 -	✓	✓	✓	✓
DP-HF1900 -	✓	✓	✓	✓

Header Tank Options				
	Single-Tank	Dual-Tank		
DP-ES1900 -	✓	×		
DP-LF1900 -	×	✓		
DP-HF1900 -	×	✓		





Above left: Single tank option | Above right: Dual tank option

Contact Us

Email: sales@digitalprintltd.com Phone: +44 (0)1604 866254

Website: www.digitalprintltd.com